

FANUC Assisted Reality (FAR)

FAR is a remote video support service that facilitates the repair or diagnosis of FANUC products. With the help of FAR, FANUC experienced service staff can see what the customer sees and thus quickly get an overview on site. Both parties are able to see video and images, talk, and draw onscreen in real-time. It is also possible to share extracts from manuals.



FEATURES



TRANSFERABLE CONTROLS

Remotely control the live camera zoom, image capture and lighting.




LOW BANDWIDTH OPTIMISED

Share live content in even the most extreme low bandwidth cellular, wireless or satellite.



HIGH QUALITY AUDIO/VIDEO

Clear audio and high quality video in even the most challenging field environments.



REMOTE CONTROLS

Remotely control the settings to adjust resolution and reduce training.



and images.

AVAILABLE FOR

TELESTRATION

PC/Laptop Tablet Mobile phone



READY FOR SMART GLASSES

TECHNICAL SPECIFICATIONS



FAR offers a highly interactive collaboration that has already proved its effectiveness internally between service technicians at FANUC. The software can be installed on an unlimited number of smartphones, tablets, smart glasses and computers. A FAR user license is required to run the software.

FAR PRODUCT SPECIFICATIONS

KEY FEATURES:

- Built to assess objects not just to see the faces of co-workers.
- Talk, freeze video, share high quality snapshots, and draw on-screen
- Record the FAR session for future record keeping or training
- Intuitive one button push to make calls
- Remotely control the live camera zoom, image capture and lighting
- Guest user service to quickly invite external collaborators
- Optimised for use with wireless, satellite and cellular networks
- Video, voice, and drawing capabilities using less than 64 kbps
- Enterprise grade security
- Central management to simplify and control deployments.
- Hosted Firewall traversal

SUPPORTED DEVICES

- Android 4.4 or higher
- iOS 10 or higher
- Windows 7.0 or higher

VIDEO

- H.264
- Resolution 160x112 up to D1:1080p
- Frame rate 1 to 30 frames per second

AUDIO

- VoIP: G.711, GSM 6.10
- Ambient Sound: G.711, GSM 6.10 (or disabled)

COMMUNICATIONS

- SIP call control (TCP 5060: TLS: 5061)
- HTTP/HTTPS (TCP 80/443)
- Audio/Video/Data (UDP)
- STUN (UDP port 3478)

RECORDINGS

- .lmc file (full featured Onsight playback)
- Export to .mov file (QuickTime playback)

IMAGES

• JPEG Format

BANDWIDTH CONTROL

- Bandwidth Test determines end to end bandwidth availability
- Real time bit stream statistics reporting
- Video bitrate: 8Kbps to 2.5Mbps
- Audio bitrate: 13.5Kbps (GSM 6.10) or 64Kbps (G.711)
- Control over maximum bandwidth limit
- Bandwidth Adaptive Streaming for performance on variable networks
- Media Configuration Details page showing bitrate distribution, data bitrate, overhead bitrate, and total bitrate

SECURITY

- SIP-TLS encryption
- AES-128 media encryption
- User ID and password control
- ISO 27001 Certified

One common serve and control platform Infinite opportunities THAT's FANUC!

FΑ

CNCs, Drives, Accessories and Software **ROBOTS**

Industrial Robots, Accessories and Software **ROBOCUT**

CNC Wire-Cut Electric Discharge Machines ROBODRILL

Compact CNC Machining Centres **ROBOSHOT**

Electric CNC Injection Moulding Machines IoT

Industry 4.0 solutions